




TRACK & HEADER DETAILS - NARROW TRACK

Straight door - Manual Operation



1. Plywood or Timber header must be fixed in a manner to support the weight of this door at 9kg m². Header to remain parallel with the floor, maximum level of tolerance +/- 5mm.

2. Optional wooden decorative trim to hide track if required "by others".

Note: Ensure there are extra header fixings in the Stack Depth Areas. Refer Jamb Details Page for Stack Depth Area Chart.

For further details contact:

Won-Door Australia Pty Ltd.
Won-Door New Zealand Ltd.


Tel: 1800 682 965
Tel: 0800 688 555

Email: info@won-door.com.au
Email: info@won-door.co.nz




JAMB DETAILS - REQUIRED (Timber stud fixing behind wall linings)

SINGLE PARTING



BI-PARTING




Stack Depth Ratio: 125mm per lineal metre of opening, PLUS 64mm for the lead post. **NOTE:** For Bi-Parting doors use half the opening width.

Stack Depth Area Calculation:

Single Parting = (Opening width (m) x 125) + 64

Bi-Parting = (1/2 Opening width (m) x 125) + 64

JAMB DETAILS - OPTIONAL (Hardwood timber jamb on face of wall linings)



1. REQUIRED: Timber stud behind wall lining centred on header to take aluminium jamb.

2. OPTIONAL: 75x20mm Hardwood timber jamb "by others" on face of wall linings. Leave a 35mm gap from the underside of plywood header, to top of hardwood jamb.

For further details contact:

Won-Door Australia Pty Ltd.
Won-Door New Zealand Ltd.

Tel: 1800 682 965
Tel: 0800 688 555

Email: info@won-door.com.au
Email: info@won-door.co.nz



FRONT ELEVATION - LEVEL FLOOR AND OBSTRUCTIONS (NARROW TRACK/HEADER)

