

STRUCTURAL SUPPORT ABOVE BY OTHERS.  
 (DOOR WEIGHT = 26.85 KGF/M<sup>2</sup> X WIDTH X HEIGHT)

13 DIA. THREADED RODS WITH NUTS & WASHERS BY  
 WON-DOOR. 248 FROM THE BACK OF THE POCKET 610 O.C.  
 IN THE OPENING AND 305 FROM THE STRIKER.  
 (1524 MAX. LENGTH INSTALLED BY WON-DOOR. LENGTHS  
 EXCEEDING 1524 ARE ACCEPTABLE WHEN INSTALLED BY  
 OTHERS)

TWO HOUR WALL CONSTRUCTION BY OTHERS. (REFER TO U.L. FIRE  
 DIRECTORY FOR CONSTRUCTION GUIDELINES.)

305 MIN. CLEARANCE REQUIRED FROM BOTTOM OF SOFFIT WALL  
 TO LOWEST OBSTRUCTION FOR PROPER TRACK CLEARANCE AND  
 ADJUSTMENTS.


TRACK ASSEMBLY BY WON-DOOR.

MOTOR DRIVE UNIT MOUNTED @ THE BACK OF THE POCKET  
 BY WON-DOOR.

POCKET COVER DOOR BY OTHERS. (SEE PLAN VIEW OR POCKET  
 DETAIL FOR SWING ORIENTATION.)

FINISHED FLOOR

SUBFLOOR



"F"  
 BOTTOM OF SOFFIT TO BOTTOM  
 OF ATTACHMENT (MAX 1524)

83 MIN.  
 REQUIRED BY U.L.

"D"

"C"

"E"

# UNITIZED HEADER DETAIL

SCALE: NO SCALE